



ISOSTATIC BEARING LIMITED



0.984 Inch | 25 Millimeter x 2.441 Inch | 62
Millimeter x 1 Inch | 25.4 Millimeter SKF E2.3305
A-2ZTN9/C3 Angular Contact Ball Bearings

Bearing No. E2.3305 A-2ZTN9/C3

E2.3305 A-2ZTN9/C3 Bearing 2D drawings and 3D
CAD models

Category	Angular Contact Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.361
EAN	7316574723188
Product Group	B00152
Enclosure	2 Metal Shields
Flush Ground	No
Rolling Element	Ball Bearing
Number of Rows of Balls	Double Row
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Polyamide
Contact Angle	30 Degree
Internal Clearance	C3-Loose
Number of Bearings	1 (Single)
Inch - Metric	Metric
Long Description	25MM Bore; 62MM Outside Diameter; 25.4MM Width; 2 Metal Shields; No Flush Ground; Ball Bearing; Double Row of Balls; ABEC 1 ISO P0; No Filling Slot;



ISOSTATIC BEARING LIMITED

	No Snap Ring; C3-Loose; Polyamide Cage; 30 Degree
Other Features	Energy Efficient Bearing
Category	Angular Contact Ball Bearing
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	E2.3305 A-2ZTN9/C3
d	0.984 Inch 25 Millimeter
B	1 Inch 25.4 Millimeter
D	2.441 Inch 62 Millimeter
bore diameter:	25 mm
cage material:	Fiberglass Reinforced Nylon
outside diameter:	62 mm
outer ring width:	25.4 mm
overall width:	1.0000 in
maximum rpm:	11000 RPM
row type & fill slot:	Double-Row Non-Fill Slot
finish/coating:	Uncoated
internal clearance:	C3
precision rating:	Not Rated
closure type:	Double Shield
fillet radius:	1 mm
radial dynamic load capacity:	32 kN
series:	E2.32
radial static load capacity:	20-2/5 kN