



ISOSTATIC BEARING LIMITED



0.472 Inch | 12 Millimeter x 1.26 Inch | 32
Millimeter x 0.626 Inch | 15.9 Millimeter SKF 3201
A-2ZTN9/C3 Angular Contact Ball Bearings

Bearing No. 3201 A-2ZTN9/C3

3201 A-2ZTN9/C3 Bearing 2D drawings and 3D CAD
models

Category	Angular Contact Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.063
EAN	7316573930761
Product Group	B00152
Enclosure	2 Metal Shields
Flush Ground	No
Rolling Element	Ball Bearing
Number of Rows of Balls	Double Row
Precision Class	ABEC 3 ISO P6
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Polymer
Contact Angle	24 Degree
Internal Clearance	C3-Loose
Number of Bearings	1 (Single)
Inch - Metric	Metric
Long Description	12MM Bore; 32MM Outside Diameter; 15.9MM Width; 2 Metal Shields; No Flush Ground; Ball Bearing; Double Row of Balls; ABEC 3 ISO P6; No Filling Slot;



ISOSTATIC BEARING LIMITED

	No Snap Ring
Category	Angular Contact Ball Bearing
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	5201 A-2ZTN9/C3
Weight / LBS	0.136
D	1.26 Inch 32 Millimeter
d	0.472 Inch 12 Millimeter
B	0.626 Inch 15.9 Millimeter
bore diameter:	12 mm
radial static load capacity:	5.6 kN
outside diameter:	32 mm
cage material:	Fiberglass Reinforced Nylon
overall width:	0.6250 in
outer ring width:	15.9 mm
contact angle:	30 °
maximum rpm:	22000 RPM
row type & fill slot:	Double-Row Non-Fill Slot
finish/coating:	Uncoated
internal clearance:	C3
precision rating:	Not Rated
closure type:	Double Shield
fillet radius:	0.6 mm
radial dynamic load capacity:	10.1 kN
series:	32