




ISOSTATIC BEARING LIMITED



5.118 Inch | 130 Millimeter x 9.055 Inch | 230
Millimeter x 2.52 Inch | 64 Millimeter SKF NU
2226 ECP/C3 Cylindrical Roller Bearings

Bearing No. NU 2226 ECP/C3

NU 2226 ECP/C3 Bearing 2D drawings and 3D CAD
models

Category	Cylindrical Roller Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	10.532
EAN	7316577723383
Product Group	B04144
Bore Profile	Straight
Cage Material	Polymer
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring - Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C3-Loose
Retainer	Yes
Relubricatable	Yes
Inch - Metric	Metric
Other Features	High Capacity Plain Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID
Long Description	130MM Bore; Straight Bore Profile; 230MM Outside Diameter; 64MM Width;



ISOSTATIC BEARING LIMITED

	Polymer Cage Material; RBEC 1 ISO P0; Single Row; Inner Ring - Both Sides Separable; No Snap Ring; Relubricatable; C3-Loose In
Category	Cylindrical Roller Bearing
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	NU 2226 ECP/C3
Weight / LBS	23.199
B	2.52 Inch 64 Millimeter
d	5.118 Inch 130 Millimeter
D	9.055 Inch 230 Millimeter
bore diameter:	130 mm
static load capacity:	735 kN
outside diameter:	230 mm
precision rating:	Not Rated
overall width:	64 mm
maximum rpm:	3400 RPM
flanges:	(2) Outer Ring
bearing material:	Steel
bore type:	Straight
cage material:	Polyamide
number of rows:	1
finish/coating:	Uncoated
internal clearance:	C3
closure type:	Open
ring separation:	Separable Ring
outer ring width:	64 mm
operating temperature range:	Maximum of +300 ° F



ISOSTATIC BEARING LIMITED

fillet radius:	2.5 mm
dynamic load capacity:	610 kN
series:	NU22